





REF.	QTY.	PART NUMBER	DESCRIPTION	MATERIAL	REMARK
1	1	See Selection Table	Shell	Epoxy FRP	White
2	2	20002478	O-ring , PWT	EPDM	
3	2	20002658	O-ring , Head	EPDM	
4	2	20000036	End Plate	ABS	
5	4	20000016	Locking Crescent	304SST	
6	2	20000004	Saddle	Engineering Thermoplastic.	
7	2	20000195	Strap	304SST-PVC	
8	4	20000206	Strap Screw	304SST	M6x60

GENERAL NOTES:

1. DIMENSIONS IN MM.
2. MAX. ANGULAR VARIATION BETWEEN ANY PORT ± 0.5 .
3. DESIGN PRESSURE: 450PSI.
4. DESIGN TEMPERATURE: Min.-7°C(20°F)-Max.65°C(149°F).
5. FOR OTHER TEMPERATURES OUT OF THIS RANGE CONTACT FIRST LINE .
6. FOR VESSEL INSTALLATION AND MAINTENANCE PLEASE REFER TO FIRST LINE USER'S MANUAL.
7. FOR REFERENCE ONLY, NOT FOR CONSTRUCTION UNLESS CERTIFIED.

Ref.	Part Number	L (MM)	S (MM)	Approx Assembly Weight (KG)
2540	R25450E-1	1100	700	3
2521	R25450E-2	617	400	2
2514	R25450E-3	439	200	1.6

First Line International Environment Technology

First Line	Design Date	Model R25-450E	
	Review Date	DRG R25-450E-00-01	
	Approval Date	Unit MM	REV. 2026