




* Parts 12 and 13 are used for 4 to 6 elements vessel only

REF.	QTY.	PART NUMBER	DESCRIPTION	MATERIAL	REMARK
1	1	See Selection Table	Shell	Epoxy FRP	White
2	2	20002478	O-ring , PWT	EPDM	
3	2	20000319	O-ring , Head	EPDM	
4	2	20000025	End Plate	ABS	1/2"x1/2"
		20000027			1/2"x3/4"
5	4	20001081	Locking Crescent	304SST	
6	4	20000205	Locking Crescent Screw	304SST	M8x10
7	1	20002813	O-ring , Plug	EPDM	
8	1	20000075	Plug	ABS	
9	2-3	20000003	Saddle	Engineering Thermoplastic.	
10	2-3	20000190	Strap	304SST-PVC	
11	4-6	20000200	Strap Screw	304SST	M8x70
12	2	20003141	Adapter	PPO	
13	4	20002478	O-ring , PWT	EPDM	



GENERAL NOTES:

1. DIMENSIONS IN MM.
2. MAX. ANGULAR VARIATION BETWEEN ANY PORT ± 0.5 .
3. DESIGN PRESSURE: 300PSI.
4. DESIGN TEMPERATURE: Min.-7°C(20°F)-Max.65°C(149°F).
5. FOR OTHER TEMPERATURES OUT OF THIS RANGE CONTACT FIRST LINE .
6. CENTER VESSEL ON 2 OR 3 SUPPORTS AT SPAN*S: 2 SUPPORTS(FOR LENGTH 1-3), 3 SUPPORTS(FOR LENGTH 4-6) .
7. FOR VESSEL INSTALLATION AND MAINTENANCE PLEASE REFER TO FIRST LINE USER'S MANUAL.
8. FOR REFERENCE ONLY, NOT FOR CONSTRUCTION UNLESS CERTIFIED.

Ref.	Part Number	L (MM)	S (MM)	Approx Assembly Weight (KG)
1	R40300E-1	1140	600	5.5
2	R40300E-2	2156	1200	8
3	R40300E-3	3172	2200	10.5
4	R40300E-4	4268	1600X2	17
5	R40300E-5	5284	2300X2	21
6	R40300E-6	6300	2700X2	25

First Line International Environment Technology

First Line	Design Date	Model R40-300E
	Review Date	
	Approval Date	DRG R40-300E-00-01
		Unit MM
		REV. 2026