






REF.	QTY.	PART NUMBER	DESCRIPTION	MATERIAL	REMARK
1	1	See Selection Table	Shell	Epoxy FRP	White
2	2~4	20002644	Feed/Conc. Port	316LSST	1.5"
2.1	2~4	20002664	Feed/Conc. Port	316LSST	2"
2.2	2~4	20002665	Feed/Conc. Port	316LSST	2.5"
3	2~4	20002424	O-ring, F/C Port	EPDM	
3.1	2~4	20002645	O-ring, F/C Port	EPDM	
3.2	2~4	20002425	O-ring, F/C Port	EPDM	
3.3	2~4	20002677	O-ring, F/C Port	EPDM	
3.4	2~4	20002426	O-ring, F/C Port	EPDM	
3.5	2~4	20002678	O-ring, F/C Port	EPDM	
4	2~4	20003264	Locknut, F/C Port	Metal	1.5"
4.1	2~4	20003265	Locknut, F/C Port	Metal	2"
4.2	2~4	20003266	Locknut, F/C Port	Metal	2.5"
5	2	20003396	Bearing Plate	Aluminium Alloy	
6	2	20003387	Sealing Plate	ABS	
7	2	20000901	O-ring, Head	EPDM	
8	4	20000314	O-ring, Adapter	EPDM	
9	1	20000314	O-ring, Plug	EPDM	
10	2	20000383	Retaining Ring	304SST	
11	1	20000073	Plug	ABS	
12	6	20000006	Locking Kit Segment	304SST	
13	6	20000196	Locking Segment Screw	304SST	M8x20
14	6	20000197	Spring Pad	304SST	$\varnothing$ 8
15	2~4	20000001	Saddle	Engineering Thermoplastic.	
16	2~4	20000186	Strap	304SST-PVC	
17	4~8	20000198	Strap Screw	304SST	M8*90
18	2	20000364	Adapter	ABS	
19	2	20000020	Shim, Adapter	ABS	2mm
20	4	20002423	O-ring, PWT	EPDM	
21	1	20000418	Thrust Ring	ABS	



GENERAL NOTES:

- DIMENSIONS IN MM.
- MAX. ANGULAR VARIATION BETWEEN ANY PORT $\pm$ 0.5.
- DESIGN PRESSURE: 450PSI.
- DESIGN TEMPERATURE: Min. -7°C(20°F)-Max. 65°C(149°F).
- FOR OTHER TEMPERATURES OUT OF THIS RANGE CONTACT FIRST LINE.
- CENTER VESSEL ON 2, 3 OR 4 SUPPORTS AT SPAN'S S*: 2 SUPPORTS(FOR LENGTH 1-3), 3 SUPPORTS(FOR LENGTH 4-6) OR 4 SUPPORTS (FOR LENGTH 7-8).
- FOR VESSEL INSTALLATION AND MAINTENANCE PLEASE REFER TO FIRST LINE USER'S MANUAL.
- FOR REFERENCE ONLY, NOT FOR CONSTRUCTION UNLESS CERTIFIED.

	PORT SIZE CODE	D(MM)	H(MM)
D	1.5" Grooved End	248	148
E	2" Grooved End	250	151
F	2.5" Grooved End	256	153

Ref.	Part Number	L (MM)	P (MM)	S (MM)	Approx Assembly Weight (KG)
1	R80450S-1	1494	1194	580	32-35
2	R80450S-2	2510	2210	1350	40-44
3	R80450S-3	3526	3226	2080	48-54
4	R80450S-4	4542	4242	1600x2	56-64
5	R80450S-5	5558	5258	2000x2	64-74
6	R80450S-6	6574	6274	2360x2	72-84
7	R80450S-7	7590	7290	2000x3	81-95
8	R80450S-8	8606	8306	2350x3	89-105

First Line International Environment Technology

First Line

Design Date	Model
Review Date	R80-450S
Approval Date	DRG
	R80-450S-00-01
	Unit
	REV.
	MM
	2026